



# Sisson's

## ALL WEATHER ACRYLIC PAINT



SIRIM  
EGO-LABEL

Low VOC &  
Heavy Metals-Free  
License No. EGO 011



High Performance  
Exterior Coating



Algae & Fungus  
Resistant



No Added  
Lead & Mercury



5

Years Warranty



# ALL WEATHER ACRYLIC PAINT

An extremely durable coating for protection of all exterior masonry surfaces against harsh weather. It is highly resistant to alkali and fungus growth. Its special acrylic binder ensures superb adhesion.


**NEW**



Birch Patina **8082**



Light Grey **8025**



Stonewall **8058**



Odyssey Blue **8075**



Mata-mata Blue **8027**



Malt White **8055**



Marble Grey **8076**

**NEW**



Tennessee Haze **8081**



Tanzania **8073**



Mystical Green **8077**



Shaded Porch **8068**



Curling Bark **8070**



Khakis **8074**

**NEW**



Terrace Stone **8080**



Autumn **8065**



Floral White **8054**




Sunflower **8026**



Pisang Emas **8043**



Sundew **8061**




Buttercup Bouquet **8072**

Also available in White 8021 & Black 8103.  
Juga terdapat dalam warna White 8021 & Black 8103.  
亦备有 White 8021 & Black 8103.



Maize **8034**




Silky White **8067**



Buff **8033**




Juliet **8032**



Off White **8015**




Warm Wheat **8050**



Cappuccino **8062**




Honey Dew **8031**



Sahara Gold **8049**



Cedar Scent **8060**



Mocha **8064**



Peach Velvet **8069**



Carrot **8045**



Colonial Brown **8063**



Stallion **8066**




Camelia **8030**



Mango **8044**



Chocolate **8048**



Tomahawk **8053**



Grey Fuchsia **8079**



Smokey Claret **8078**

All colours are intermixable. Colours presented are as close as modern printing techniques allow.  
 Semua warna boleh dicampur-aduk. Warna yang tertera adalah sehampir mana yang dibenarkan oleh teknik pencetakan moden.  
 所有颜色皆可混合。所示色彩是现代印刷技术所能达至的最接近的颜色。

All Weather Acrylic Paint is an extremely durable coating for protection and decoration of all exterior masonry surfaces. It is extremely resistant to fungus growth and attack from alkali. Its special acrylic binder also ensures excellent adhesion of paint to the substrate.

**Surface Preparation:** Wall surfaces to be painted must be clean and dry. Remove all loose materials with a stiff fibre brush under running water or a high pressure water jet. All Weather Acrylic Paint is a self priming finish. Where high alkalinity is present, apply 1 coat of Sissons Alkali Resisting 'D' Primer.

**Thinning:** The paint is ready for use, but for absorbent surfaces, the paint should be thinned 5-10% by volume with water to assist application of the first coat. On subsequent coats no thinning is required for application by brush. 5% thinning is sufficient to assist roller application under normal circumstances.

**Application:** Suitable for applications by brush, roller or spray.

**Drying Time:** Approximately 2 hours.

**Number Of Coats:** 2 coats.

**Coverage:** Approximately 11 sq. metres per litre.

**Cleaning Up:** Clean with clean water immediately after use.

All Weather Akrilik ialah cat yang mampu bertahan lama untuk perlindungan dan mengindahkan semua bahagian permukaan berbatu luar. Ia tahan serangan kulat dan alkali. Pengikat akrilik juga memastikan perlekatan cat yang sempurna.

**Persediaan Pada Permukaan:** Permukaan dinding yang hendak dicat mestilah bersih dan kering. Buangkan bahan-bahan yang mengelupas dengan berus sabut yang keras berserta dengan air atau dengan tekanan air yang tinggi. Cat All Weather Akrilik memberikan kemasam yang tersendiri. Di mana terdapatnya keadaan beralkali tinggi, sapukan satu (1) lapisan Sissons Alkali Resisting 'D' Primer terlebih dahulu.

**Pencairan:** Cat sedia digunakan tapi bagi permukaan yang boleh menyerap cecair, cat perlu dicairkan 5-10% dengan air bagi memudahkan kerja-kerja mengecat lapisan pertama. Pada lapisan seterusnya, cat tidak perlu dicairkan jika proses mengecat menggunakan berus. 5% pencairan adalah memadai bagi memudahkan kerja mengecat menggunakan pengelek ke atas permukaan berkeadaan biasa.

**Penggunaan:** Sesuai untuk penggunaan berus, pengelek atau semburan.

**Tempoh Pengeringan:** Anggaran 2 jam.

**Jumlah Lapisan:** 2 lapisan.

**Kadar Luas Penggunaan:** Anggaran 11 meter persegi seliter.

**Pembersihan:** Bersihkan dengan air sebaik sahaja selepas digunakan.

丙烯酸质的晴雨漆是一种超强耐久的涂层。可有效保护及修饰室外的砖石屋瓦等表面。它拥有高度排除真菌类植物的生长以及碱性的侵蚀。它独特的丙烯酸结合剂也可确保漆料可以牢固地紧贴着底层。

**表面处理:** 要涂漆的墙面必须清结及干净。用流水和坚硬的干纤维刷或高压水枪除去所有的松散物质。时新全天候丙烯酸漆本身就是基涂。如果是高碱性的地方, 可先涂一层时新防碱'D'基涂。

**稀释:** 此漆料已调配好, 可即时应用; 但如果是吸收力强的表层, 则必须在第一次涂漆时先以漆量5-10%的清水稀释。接下来涂漆若使用毛刷就无需再稀释; 若使用滚筒则在一般的情况下需以5%清水稀释。

**应用方法:** 适宜使用毛刷、滚筒或喷射方式。

**干透时间:** 大约2小时。

**涂漆层数:** 2层。

**用量:** 每公升大约可涂漆11平方公尺。

**清洗:** 使用后需即刻以清水清洗。

Also available from:



**omnicolor**  
Sissons Computerized Tinting Machine